



FEATURES

- 5" **DIGITAL** TFT LCD Monitor
- Aluminum Die Cast Housing
- Free Input Voltage (DC 10V ~ 30V)
- NTSC / PAL Compatibility
- 3 Camera Inputs & 3 Triggers (CA1 shutter camera compatible)
- Parking Line
- Waterproof Housing (IP-68)
- Built-in the Reverse Polarity Protection Circuit
- Built-in Speaker
- Temp. -20 ~ 70°C

SPECIFICATIONS

LCD Screen Size	5" Digital TFT LCD
Dimension (W x H x D)	105 x 152 x 23(mm)
Power Source	DC 10V ~ 30V / 400mA Max.
Video System	NTSC / PAL Auto Detection
Sync. System	Internal
Scanning Line	640 X (RGB) X 480
Viewing Angle	Top: 50°, Bottom: 70°, Left: 70°, Right: 70°
Color Configuration	RGB Stripe
Parking Line	Automatic display by R gear or Off Parking Line Width Adjustable
Dimmer	Manual
Speaker Impedance	8 ohm, 1.0 Watt Max.
Operating Temperature	-20°C to +70°C
Impact Rating	7 G
Camera Connector	4-Pin Mini-DIN
Housing	Aluminum Die Cast Housing
On-Screen Display Control Functions	Volume, Brightness, Color, Contrast, Tint, CAM Trigger, CAM Distance, Language, Reset
Weight	480g
Supplied Accessories	- Stand Bracket - Camera Input Cable