

FEATURES

- High Resolution 8" **DIGITAL** TFT LCD Monitor
- Free Input Voltage (DC 10V ~ 30V)
- NTSC / PAL Compatibility
- 3 Camera Inputs & 3 Triggers
(CA1/2/3 shutter camera compatible)
- Single display mode(by Trigger Mode)
- 2 types Parking Line
- Waterproof Housing (IP-64)
- Rubber Touch Neutral Black Housing
- Automatic Brightness Sensor (Day & Night)
- Built-in the Reverse Polarity Protection Circuit
- Built-in Speaker
- Speed Switch Function
- Shutter Memory Function



SPECIFICATIONS

LCD Screen Size	8" Digital TFT LCD (16 : 9)
Power Source	DC 10V ~ 30V / 12Watt. Max.
Video System	NTSC / PAL Compatibility
Sync. System	Internal
Scanning Line	800 X (RGB) X 480
Viewing Angle	Top: 50°, Bottom: 70°, Left: 70°, Right: 70°
Color Configuration	RGB Stripe
Dimmer	Automatic / Manual
Speaker Impedance	8 ohm, 1.0 Watt Max.
Operating Temperature	-20°C to +70°C
Impact Rating	4 G
Camera Connector	4-Pin Mini-DIN
Housing	Rubber Touch Neutral Black
On-Screen Display Control Functions	Volume, Brightness, Color, Contrast, Hue, CAM Trigger, Parking Line, Dimmer, Language, Factory Reset
Dimension (W x H x D)	233(W) x 143(H) x 26(D) mm
Weight	650 g
Supplied Accessories	- Stand Bracket - Sun Shield - Camera Input Cable